

Basics of C++ and object orientation in OpenFOAM

- To begin with: The aim of this part of the course is not to teach all of C++, but to give a short introduction that is useful when trying to understand the contents of OpenFOAM.
- After this introduction you should be able to *recognize* and make *minor modifications* to most C++ features in OpenFOAM.
- We will first have a quick look at a piece of code in OpenFOAM, then we will follow the book *C++ direkt* by Jan Skansholm (ISBN 91-44-01463-5)

Basic layout of files in OpenFOAM (magU)

- All OpenFOAM applications and libraries start with a commented section:

```

/*-----*\
=====
\\      /  F i e l d      |  OpenFOAM: The Open Source CFD Toolbox
  \\      /  O p e r a t i o n  |
    \\      /  A n d          |  Copyright (C) 1991-2007 OpenCFD Ltd.
      \\\/      M a n i p u l a t i o n  |
-----\
...
Some descriptive text
...
\*-----*/

```

- The first lines of an application or a library (after the above commented section) includes header files for the libraries of classes that will be used in the code. In OpenFOAM, all the general classes for *finite volume* CFD are added by:

```
#include "fvCFD.H"
```

This file contains only the declarations in the library, while the actual contents of the library is linked to at run-time.

Basic layout of files in OpenFOAM (magU)

- The file `fvCFD.H` is *included* in the code according to the description in the `Make/options` file:

```
EXE_INC = \  
    -I$(LIB_SRC)/finiteVolume/lnInclude
```

i.e. `$WM_PROJECT_DIR/src/finiteVolume/lnInclude/fvCFD.H`, and the libraries are linked according to the description in the `Make/options` file:

```
EXE_LIBS = \  
    -lfiniteVolume
```

and the path to the library is found using the Linux environment variables:

```
ldd 'which magU'  
libfiniteVolume.so =>  
    /local/hani/OpenFOAM/OpenFOAM-1.4.1/lib/  
    linux64GccDPOpt/libfiniteVolume.so
```

This library must be present both during compilation and at run-time, since OpenFOAM uses dynamic libraries.

Basic layout of files in OpenFOAM (magU)

- The file `fvCFD.H` starts with the following lines:

```
#ifndef fvCFD_H
#define fvCFD_H
```

which makes sure that the file will not 'execute' more than once, although it may be included multiple times. There is an `#endif` at the end of the file, terminating this if-statement.

- The file `fvCFD.H` continues with a number of include-statements, and it ends with:

```
#ifndef namespaceFoam
#define namespaceFoam
    using namespace Foam;
#endif
```

which defines the namespace `Foam` if it has not already been defined. I.e. all declarations made in the included library belong to the namespace `Foam`, and the present code should use namespace `Foam`.

Basic layout of files in OpenFOAM (magU)

- A C++ code must contain exactly one instance of the function `main`, and the execution of the code starts in this function.
- In OpenFOAM the `main` function takes parameters and returns an integer:

```
int main(int argc, char *argv[])
```

The arguments you give when starting an executable are thus passed on to the `main` function. There are `argc` number of arguments, and they are located in the `argv` list, which is used in the code.

- The body of the `main` function is embraced by:

```
{  
  
.....  
  
    return(0);  
}
```

where the dots represent the code, and the `return` statement returns the integer 0 when finishing the `main` function.

C++ basics

- Variables can contain data of different *types*, for instance `int myInteger;` for a declaration of an integer variable named `myInteger`, or `const int myConstantInteger = 10;` for a declaration of an *constant* integer variable named `myConstantInteger` with value 10. In C++ it is possible to define special *types*, and there are many types defined for you in OpenFOAM.
- Input and output can be done using the standard library `iostream`, using:

```
cout << "Please type an integer!" << endl;  
cin >> myInteger;
```

where `<<` and `>>` are output and input operators, and `endl` is a manipulator that generates a new line (there are many other manipulators). In OpenFOAM a new output stream `Info` is however defined, and it is recommended to use that one instead since it takes care of write-outs for parallel simulations.

- Variables can be added, substracted, multiplied and divided as long as they have the same type, or if the types have definitions on how to convert between the types. User-defined types must have the required conversions defined. Some of the types in OpenFOAM can be used together in arithmetic expressions, but not all of them.

C++ basics

- `+`, `-`, `*` and `/` are operators that define how the operands should be used. Other standard operators are `%` (integer division modulus), `++` (add 1), `--` (subtract 1), `+=` (`i+=2` adds 2 to `i`), `-=`, `*=`, `/=`, `%=` etc. User-defined types should define its operators.
- Mathematic standard functions are available in standard libraries. They are thus not part of C++ itself.
Standard library `cmath` contains trigonometric functions, logarithmic functions and square root. (use `#include <cmath>`; if you need them)
Standard library `cstdlib` contains general functions, and some of them can be used for arithmetics. (use `#include <cstdlib>`; if you need them)
- **if-statements:** `if (variable1 > variable2) {...CODE...} else {...CODE...}`
Comparing operators: `<` `>` `<=` `>=` `==` `!=`
Logical operators: `&&` `||` `!` (or, for some compilers: `and` `or` `not`)
Generates `bool` (boolean)
- **while-statements:** `while (...expression...) {...CODE...}`
- `break;` breaks the execution of `while`

C++ basics

- **for-statements:** `for (init; condition; change) {...CODE...}`
- **Arrays:**
`double f[5];` (Note: components numbered from 0!)
`f[3] = 2.75;` (Note: no index control!)
`int a[6] = {2, 2, 2, 5, 5, 0};` (declaration and initialization)
The arrays have strong limitations, but serve as a base for array **templates**
- **Array templates** (example `vector`. other: `list`, `deque`):
`#include <vector>`
`using namespace std`
The type of the vector must be specified upon declaration:
`vector<double> v2(3);` gives {0, 0, 0}
`vector<double> v3(4, 1.5);` gives {1.5, 1.5, 1.5, 1.5}
`vector<double> v4(v3);` gives a copy of v4
- **Array template operations:** The template classes define member functions that can be used for those types, for instance: `size()`, `empty()`, `assign()`, `push_back()`, `pop_back()`, `front()`, `clear()`, `capacity()` etc.
`v.assign(4, 1.0);` gives {1.0, 1.0, 1.0, 1.0}

C++ basics

- Functions may, or may not, return a value
- Example function average

```
double average (double x1, double x2)
{
    int nvalues = 2;
    return (x1+x2)/nvalues;
}
```

takes two arguments of type `double`, and returns type `double`. The variable `nvalues` is a local variable, and is only visible inside the function. Note that any code after the `return` statement will not be executed.

- A function doesn't have to take arguments, and it doesn't have to return anything (the output type is then specified as `void`). The `main` function should return an integer, but it is alright to skip the `return` statement in the `main` function.
- There may be several functions with the same names, as long as there is a difference in the arguments to the functions - the number of arguments or the types of the arguments.

C++ basics, scope of variables

- The scope and visibility of a variable depends on where it is defined.
A variable defined in a block (between { }) is visible in that block.
A variable defined in a function head (arguments) is visible in the entire function.
Other scopes are classes and name spaces, which we might discuss later.
There can be several variables with the same name, but only one in each block.
It is possible to use a global variable even if there is a local variable with the same name in the current block. The operator :: is then used (::x)

Example:

```
int x;  
int f1(char c)  
{  
    double y;  
    while (y>0)  
    {  
        char x;  
    }  
    int w;  
}
```

C++ basics, declaration of variables and functions

- Variables and functions must be *declared* before they can be used. Example:

```
double average (double x1, double x2)
main ()
{
    mv = average(value1, value2)
}
double average (double x1, double x2)
{
    return (x1+x2)/2;
}
```

The second occurrence of the function head is the definition of the function. The argument names may be omitted in the declaration.

- Declarations are often included from include-files (`#include "file.h"` or `#include <standardfile>`)
- A good way to program C++ is to make files in pairs, one with the declaration, and one with the definition. This is done throughout OpenFOAM.

C++ basics, function parameters / arguments

- If an argument variable should be changed inside a function, the type of the argument must be a reference, i.e.

```
void change(double& x1)
```

The reference parameter `x1` will now be a reference to the argument to the function instead of a local variable in the function. (standard arrays are always treated as reference parameters).

- Reference parameters can also be used to avoid copying of large fields when calling a function. To avoid changing the parameter in the function it can be declared as `const`, i.e.

```
void checkWord(const string& s)
```

This often applies for parameters of class-type, which can be large.

- Default values can be specified, and then the function may be called without that parameter, i.e.

```
void checkWord(const string& s, int nmb=1)
```

C++ basics, Types

- *Types* define what values a variable may obtain, and what operations may be made on the variable.
- Pre-defined C++ types are:

```
signed char  
short int  
int  
unsigned char  
unsigned short int  
unsigned int  
unsigned long int  
float  
double  
long double
```

- User defined types can be defined in *classes*. OpenFOAM provides numerous types that are useful for solving partial differential equations.

C++ basics, Pointers

- Pointers point at a memory location.
- A pointer is recognized by its definition (*):

```
int *pint;  
double *pdouble;  
char *pchar;
```
- Turbulence models are treated with the `turbulence` pointer in OpenFOAM.
- We will not discuss pointers any further at the moment.

C++ basics, typedef

- Type declarations in C++ may be quite complicated. By using `typedef`, the type can be given a new name, i.e.

```
typedef vector<int> integerVector;
```

An integer vector can then simply be defined as

```
integerVector iV;
```

This is used to a large extent in OpenFOAM, and the reason for this is to make the code easier to read.

C++ basics, object orientation

- Object orientation focuses on the objects instead of the functions.
- An *object* belongs to a *class* of objects with the same attributes. The class defines the construction of the object, destruction of the object, attributes of the object and the functions that can manipulate the object.
- The objects may be related in different ways, and the classes may inherit attributes from other classes.
- A benefit of object orientation is that the classes can be re-used, and that each class can be designed and bug-fixed for a specific task.
- In C++ a *class* is the same thing as a *type*, so the classes can be seen as new types that are designed for specific tasks.
- In OpenFOAM, the classes are designed to define, discretize and solve PDE's.

C++ basics, class definition

- The following structure defines the class `Name` and its public and hidden member functions and member data.

```
class name {  
public:  
    declarations of public member functions and data members  
private:  
    declaration of hidden member functions and data members  
};
```

- `public` attributes are visible from outside the class.
- `private` attributes are only visible within the class.
- In neither `public` nor `private` are specified, all attributes will be `private`.
- Declarations of member functions and data members are done as usual.

C++ basics, using a class

- An object of a class `name` is defined in the main code as:
`name nameObject; (c.f. int i)`
- `nameObject` will then have all the attributes defined in the class `name`.
- Any number of objects may belong to a class, and the attributes of each object will be separated.
- There may be pointers and references to any object.
- The member functions operate on the object according to its implementation.
If there is a member function `write` that writes out the contents of an object of the class `name`, it is called in the main code as:
- When using the memberfunctions through a pointer, the syntax is slightly different (here `p1` is a pointer to the object `nameObject`, and `p2` is a pointer to a nameless new `name`:

```
p1 = &nameObject;  
p2 = new name;  
p1->write();  
p2->write();
```

C++ basics, member functions

- The member functions may be defined either in the definition of the class, or outside the definition of the class. We will see this when we look inside OpenFOAM. The syntax is basically:

```
inline void name::write()  
{  
    Contents of the member function.  
}
```

where `name::` tells us that the member function `write` belongs to the class `name`., `void` tells us that the function does not return anything, and `inline` tells us that the function will be *inlined* into the code where it is called instead of jumping to the memory location of the function at each call (good for small functions). Member functions defined directly in the class definition will automatically be inlined if possible.

- The member functions have direct access to all the data members and member functions of the class.

C++ basics, organization of classes

- A good programming standard is to make the class files in pairs, one with the class definition, and one with the function declarations.
- Classes that are closely related to each other can share files, but keep the class definitions and function declarations separate. This is done throughout OpenFOAM.
- The class definitions must be `included` in the object file that will use the class, and in the function declarations file. The object file from the compilation of the declaration file is statically or dynamically linked to the executable by the compiler.
- Inline functions must be implemented in the class definition file, since they must be inlined without looking at the function declaration file. In OpenFOAM there are usually files named as `VectorI.H` containing `inline` functions, and those files are included in the corresponding `Vector.H` file.

C++ basics, OpenFOAM examples

- `src/OpenFOAM/primitives/Vector`

C++ basics, Constructors

- A constructor is a special initialization function that is called each time a new object of that class is defined. Without a specific constructor all attributes will be undefined. A null constructor must always be defined.
- A constructor can be used to initialize the attributes of the object. A constructor is recognized by it having the same name as the class (here `Vector`. `Cmpt` is typedef for component type, i.e. the `Vector` class works for all component types):

```
// Constructors
  //- Construct null
  inline Vector();
  //- Construct given VectorSpace
  inline Vector(const VectorSpace<Vector<Cmpt>, Cmpt, 3>&);
  //- Construct given three components
  inline Vector(const Cmpt& vx, const Cmpt& vy, const Cmpt& vz);
  //- Construct from Istream
  inline Vector(Istream&);
```

- The vector will be initialized differently depending on which of these constructors is chosen.

C++ basics, Constructors

- The actual initialization usually takes place in the corresponding .C file, but since the constructors for the `Vector` are inlined, it takes place in the `VectorI.H` file:

```
// Construct given three Cmpts
template <class Cmpt>
inline Vector<Cmpt>::Vector(const Cmpt& vx, const Cmpt& vy, const Cmpt& vz)
{
    this->v_[X] = vx;
    this->v_[Y] = vy;
    this->v_[Z] = vz;
}
```

(here `this` is a pointer to the current object of the current class, i.e. we here set the static data member `v_` (inherited from class `VectorSpace.H`) to the values supplied as arguments to the constructor.

- It is here obvious that the member function `Vector` belongs to the class `Vector`, and that it is a constructor since it has the same name as the class.

C++ basics, Constructors

- A copy constructor has a parameter that is a reference to another object of the same class. (`className(const className&);`). The copy constructor copies all attributes. A copy constructor can only be used when initializing an object (since a constructor 'constructs' a new object). Usually there is no need to define a copy destructor since the default one does what you need. There are however exceptions.
- A type conversion constructor is a constructor that takes a single parameter of a different class than the current class, and it describes explicitly how to convert between the two classes. (There can actually be more parameters, but then they have to have default values)

C++ basics, Destructors

- When using dynamically allocated memory it is important to be able to destruct an object.
- A destructor is a member function without parameters, with the same name as the class, but with a `~` in front of it.
- An object should be destructed when leaving the block it was constructed in, or if it was allocated with `new` it should be deleted with `delete`
- To make sure that all the memory is returned it is preferable to define the destructor explicitly.

C++ basics, Constant member functions

- An object of a class can be constant (`const`). Some member functions might not change the object (*constant functions*), but we need to tell the compiler that it doesn't. That is done by adding `const` after the parameter list in the function definition. Then the function can be used for constant objects:

```
template <class Cmpt>
inline const Cmpt&  Vector<Cmpt>::x() const
{
    return this->v_[X];
}
```

This function returns a *constant* reference to the X-component of the object (first `const`) without modifying the original object (second `const`)

C++ basics, Friends

- A friend is a function (not a member function) or class that has access to the private members of a particular class.
- A class can invite a function or another class to be its friend, but it cannot require to be a friend of another class.

C++ basics, Operators

- Operators define how to manipulate objects.
- Standard operator symbols are:

```

new   delete   new[]   delete[]
+     -     *     /     %     ^     &     |     ~
!     =     <     >     +=    -=    *=    /=    %=
^=    &=    |=    <<    >>    >>=   <<<=   ==    !=
<=    >=    &&    ||    ++    --    ,     ->*   ->
()    []

```

When defining operators, one of these must be used.

- Operators are defined as member functions or friend functions with name `operatorX`, where `X` is an operator symbol.
- OpenFOAM has defined operators for all classes, including `iostream << and >>`

C++ basics, Static members

- Static members of a class only exist in a single instance in a class, for all objects, i.e. it will be equivalent in all objects of the class.
- They are defined as `static`, which can be applied to data members or member functions.
- Static members do not belong to any particular object, but to a particular class, so they are used as:

```
className::staticFunction(parameters);
```

(They can actually also be used as `object.staticFunction(parameters)`, but that would be a bit mis-leading since nothing happens explicitly to `object`, and that all objects of the class will notice the effect of the `staticFunction`)

C++ basics, Inheritance

- A class can inherit attributes from already existing classes, and extend with new attributes.
- Syntax, when defining the new class:

```
class newClass : public oldClass { ...members... }
```

where `newClass` will inherit all the attributes from `oldClass`.
`newClass` is now a *sub class* to `oldClass`.

- OpenFOAM example:

```
template <class Cmpt>  
class Vector  
{  
    public VectorSpace<Vector<Cmpt>, Cmpt, 3>  
};
```

where `Vector` is a sub class to `VectorSpace`.

- A member of `newClass` may have the same name as one in `oldClass`. Then the `newClass` member will be used for `newClass` objects and the `oldClass` member will be hidden. Note that for member functions, all of them with the same name will be hidden, irrespectively of the number of parameters.

C++ basics, Inheritance/visibility

- A hidden member of a base class can be reached by `oldClass::member`
- Members of a class can be `public`, `private` or `protected`.
- `private` members are never visible in a sub class, while `public` and `protected` are. However, `protected` are only visible in a sub class (not in other classes).
- The visibility of the inherited members can be modified in the new class using the reserved words `public`, `private` or `protected` when defining the class. (`public` in the previous example). It is only possible to make the members of a base class *less visible* in the sub class.
- A class may be a sub class to several base classes (multiple inheritance), and this is used to combine features from several classes. Watch out for ambiguous (tvetydiga) members!

C++ basics, Virtual member functions

- Virtual member functions are used for dynamic binding, i.e. the function will work differently depending on how it is called, and it is determined at run-time.
- The reserved word `virtual` is used in front of the member function declaration to declare it as virtual.
- A sub-class to a class with a virtual function should have a member function with the same name and parameters, and return the same type as the virtual function. That sub-class member function will automatically be a virtual function.
- By defining a pointer to the base class a dynamic binding can be realized. The pointer can be made to point at any of the sub-classes to the base class.
- The pointer to a specific sub class is defined as: `p = new subClass (...parameters...)`.
- Member functions are used as `p->memberFunction` (since `p` is a pointer)
- OpenFOAM uses this to dynamically choose turbulence model.
- Virtual functions make it easy to add new turbulence models without changing the original classes (as long as the correct virtual functions are defined).

C++ basics, Abstract classes

- A class with at least one virtual member function that is undefined (a *pure* virtual function) is an abstract class.
- The purpose of an abstract class is to define how the sub classes should be defined.
- An object can not be created for an abstract class.
- The OpenFOAM `turbulenceModel` is such an abstract class since it has a number of pure member functions, such as

```
//- Return the turbulence viscosity  
virtual tmp<volScalarField> nut() const = 0;
```

(you see that it is *pure* virtual by '= 0').

C++ basics, Container classes

- A container class contains and handles data collections. It can be viewed as a list of entries of objects of a specific class. A container class is a sort of *template*, and can thus be used for objects of any class.
- The member functions of a container class are called *algorithms*. There are algorithms that search and sort the data collection etc.
- Both the container classes and the algorithms use *iterators*, which are pointer-like objects.
- The container classes in OpenFOAM can be found in `src/OpenFOAM/containers`, for example `UList`
- `forAll` is defined to help us march through all entries of a list of objects of any class.

C++ basics, Templates

- The most obvious way to define a class is to define it for a specific type of object. However, often similar operations are needed regardless of the object type. Instead of writing a number of identical classes where only the object type differs, a generic *template* can be defined. The compiler then defines all the specific classes that are needed.
- Container classes should be implemented as class templates, so that they can be used for any object. (i.e. List of integers, List of vectors ...)
- Function templates define generic functions that work for any object.
- A template class is defined by a line in front of the class definition, similar to:

```
template<class T>
```

where `T` is the generic parameter (there can be several in a 'comma' separated list), defining *any* type. The word `class` defines `T` as a *type* parameter.

- The generic parameter(s) are then used in the class definition instead of the specific type name(s).
- A template class is used to construct an object as:

```
templateClass<type> templateClassObject;
```

C++ basics, typedef

- OpenFOAM is full of templates.
- To make the code easier to read OpenFOAM re-defines the templated class names, for instance:

```
typedef List<vector> vectorList;
```

so that an object of the class template `List` of type `vector` is called `vectorList`.

C++ basics, Namespace

- When using pieces of C++ code developed by different programmers there is a risk that the same name has been used for the same declaration, for instance two constants with the name `size`.
- By associating a declaration with a namespace the declaration will only be visible if that namespace is used. Remember that the standard declarations are used by starting with:

```
using namespace std;
```

- OpenFOAM declarations belong to namespace `Foam`, so in OpenFOAM we use:

```
using namespace Foam;
```

to make all declarations in namespace `Foam` visible.

- **Explicit naming in OpenFOAM:**

```
Foam::function();
```

where `function()` is a function defined in namespace `Foam`. This must be used if any other namespace containing a declaration of another `function()` is also visible.

C++ basics, Namespace

- A namespace with the name `name` is defined as

```
namespace name {  
    declarations  
}
```

- New declarations can be added to the namespace using the same syntax in another part of the code.