

Post-processing in paraFoam

- paraFoam is the main post-processor, distributed with OpenFOAM. As previously mentioned, you can also use other alternatives. However, paraFoam is quite powerful and competitive with commercial alternatives, and it is based on OpenSource software.
- paraFoam is a wrapper for the third-party product Paraview (www.paraview.org). It basically generates a file named `<case>.OpenFOAM`, which is necessary since Paraview needs a file to be specified. paraFoam also makes sure that the OpenFOAM reader is used, and that the paraview GUI is modified according to the specifications for OpenFOAM.
- Paraview is based on VTK, the visualization toolkit (www.vtk.org)
- Results from OpenFOAM can be converted to the VTK format using `foamToVTK`. In some cases, like for lagrangian particle tracking, this is in fact necessary.
- References: The ParaView Guide, ISBN 1-930934-21-1, VTK User's Guide, ISBN 1-930934-13-0, The Visualization Toolkit, ISBN 1-930934-12-2, Programming Python, ISBN 0-596-00085-5.

Post-processing the icoFoam/cavity case in paraFoam

In the following, we will use paraview 3.8.0 and the OpenFOAM reader compiled with OpenFOAM.

- We will now do some post-processing of the `icoFoam/cavity` case, with the purpose of learning the basics of Paraview.
- Go to the `icoFoam/cavity` case that we have already run:

```
cd $FOAM_RUN/cavity
```
- Type `paraFoam` to post-process that case.
- The case name will appear as the object `cavity.OpenFOAM` in the Pipeline Browser.
- If you do an `ls -l` in the case directory you will see that a temporary empty file named `cavity.OpenFOAM` has been generated.
- The object can be controlled using the `Object Inspector`, which we will discuss in the coming slides...

paraFoam, Properties tag

- In `Mesh Parts`, check what parts of the mesh should be imported.
- In `Volume Fields`, check what volume fields should be imported.
- Click on `Patch Names` if you want to view them.
- Click on `Include Sets` and/or `Include Zones` if you have sets or zones that you want to visualize. This is very useful in order to check if your sets and zones have been generated properly. However, in the `cavity` case, we have no sets or zones.
- Click `Apply` to read in the mesh and the volume fields.
- If the contents of your case directory has changed, click on `Update GUI` and `Apply` to import the new information.

paraFoam, Display tag

- Control visibility (can also be done by clicking on the 'eye' in the Pipeline Browser).
- Color the object by a constant color, or using a variable. For cell based representation, the variables are assumed to constant in each cell, and for point based representation, the variables are interpolated to the points, yielding a smooth field. The colormap can be edited, and the color range can be re-scaled. In `Edit Colormap` (and in the view menu), a `Color Legend` can be added. The color legend can be moved and re-scaled with the mouse.
- The representation of the object can be as outline, wireframe, surface etc.
- The cartesian extent of the object is shown by clicking on `Show cube axes`. This representation can be edited.
- The object can be translated, which is useful when comparing results from different simulations of the same case, or when viewing the same case in different angles.

paraFoam, Information tag

- Here you get some information on the mesh and the fields.

paraFoam, Visualization window

- Rotate by holding the left mouse key, and moving the mouse. It is like rolling a ball.
- Zoom by holding the right mouse key, and moving the mouse up and down.
- Move by holding the center mouse key, and moving the mouse.

paraFoam, Visualization window

- At the top left of the visualization window, you can see five icons:



- No1: Undo last visualization transformation.
- No2: Redo last undone visualization transformation.
- No3: Edit View Options (background color, parallel projection, lights, toggle axes - if 'interactive', you can move them with the mouse).
- No4: NOT IN 3.8.0, INSTEAD YOU CAN DEFINE FOUR CAMERA VIEWS IN THE FIFTH ICON! (Before: Lookmark (if you want to save a view))
- No5: Adjust Camera (use standard views, or adjust the views).

paraFoam, Visualization window

- At the top right of the visualization window, you can see four icons:



- No1: Split Horizontal.
- No2: Split Vertical.
- No3: Maximize (only useful if there are multiple visualization windows).
- No4: Close (only useful if there are multiple visualization windows).


paraFoam, Filters

- The Filters/Alphabetical menu lets you manage your data in different ways. Some of those can be selected by the icons:






- We will have a look at some of them in the next slides...



paraFoam, Calculator Filter

- With the Calculator filter  you can create new fields from existing scalar and vector fields, using simple mathematical functions.
- The new fields can be used just like the original fields.



paraFoam, Contour, Clip and Slice Filters

- The Contour Filter  lets you make a contour plot or iso-surface, if the parent object is 2D or 3D, respectively.
- The Clip Filter  lets you clip your results using plane/box/sphere/scalar.
- The Slice Filter  lets you make a plane/box/sphere cuts through your results.
 - It is possible to specify the plane in different ways.
 - Multiple cuts can be made simultaneously using Slice Offset Values.
 - Each Slice will generate a new object in the Pipeline Browser, which can be colored etc. like any other object.

paraFoam, Threshold, Glyph and Cell Center Filters

- The Threshold Filter  lets you show cells with solution scalar values in a specific range.
- The Glyph Filter  lets you make vector plots. It can also be used to visualize lagrangian particles.
 - Glyphs are by default generated at the grid points. If you want the vectors to be located in the center of the cells, you first need to make a new object of the cell centers using the Cell Centers filter.
 - Mark the cell centered object, and filter it with the default values of the Glyph Filter.
 - It is possible to modify the representation of the vectors in the Properties tag.

paraFoam, Stream Tracer and Warp Filters

- The Stream Tracer filter  lets you make streamline tracers, submitted from a point, a spherical cloud, or line sources.
- The Warp (scalar) filter  lets you distort your geometry according to the local value of a scalar. This is mostly useful in solid mechanics.

paraFoam, Plot Over Line Filter

- The Plot Over Line filter lets you make detailed plots of the variables along a line.
- In the Display tab, you can choose which variables to plot, and choose line colors and line styles.
- Later on we will learn how to extract line data using the OpenFOAM sample utility, and plot it in OpenSource Gnuplot, www.gnuplot.info, (or any other plotter).

paraFoam, Image output

- `File/Save Screenshot` saves pixel images in a number of formats: `png`, `bmp`, `tiff`, `ppm`, `jpg`, `pdf`
- The format is chosen by the extension of the filename.
- Increase the resolution for high quality images.
- Use `ls -l` to see the difference in file size for the different formats.
- Use `gimp` to view and edit all the image formats.
- Convert to `eps` format for inclusion in `LATEX` documents using:
`/usr/bin/convert test.jpg test.eps`
(we specify the whole path to make sure that we use the correct one)
- View the `eps` file using `gv`.

paraFoam, Animation output

- File/Save Animation saves frame images in a number of formats:
jpg, tiff, png
- Use `/usr/bin/convert` to convert the frame images into a movie:
`/usr/bin/convert -quality 90% frames*.png movie.gif`
- View the movie using `firefox file://$PWD/movie.gif`
- Increase the resolution for high quality animations.

paraFoam, Save and Load states

- The current state, including created objects and current view, can be saved for later loading. This is useful if the same visualization needs to be done many times.
- Saved states can be loaded directly from `paraview`, so there is no need to run `paraFoam`.
- State files are in ASCII, so it is possible to generate or modify them externally if needed.

paraFoam, Multiple cases

- Multiple OpenFOAM cases can be read into paraFoam.
- For the additional cases you must generate the <case>.OpenFOAM file by hand:

```
touch $FOAM_RUN/<case>/<case>.OpenFOAM
```
- Launch paraFoam with the first case as usual.
- Read in the additional cases in paraFoam using File/Open
- This procedure can also be used to view cases that are decomposed for parallel simulation, in order to see the domain decomposition. Then you generate a processor*.OpenFOAM file in each processor* directory. We will discuss parallel simulations later.
- This is also the procedure for multi-region cases, like conjugate heat transfer and fluid-structure interaction.