

DETACHED EDDY SIMULATIONS: ANALYSIS OF A LIMIT ON THE DISSIPATION TERM FOR REDUCING SPECTRAL ENERGY TRANSFER AT CUT-OFF

Lars Davidson*, Christophe Friess**

*Division of Fluid Dynamics
Dept. of Mechanics and Maritime Sciences
SE-412 96 Gothenburg, Sweden

**Aix-Marseille Université
CNRS, Centrale Marseille
M2P2 UMR 7340, 13451, Marseille, France

December 11, 2021

(ID)DES: PHYSICAL MEANING OF ψ

$$C^k = P^k + D^k - \psi \varepsilon$$

k – equation

$$C^\varepsilon = C_{\varepsilon 1} \frac{\varepsilon}{k} P^k + D^\varepsilon - C_{\varepsilon 2} \frac{\varepsilon^2}{k}$$

ε – equation

$$\psi = \max \left(1, \frac{k^{3/2}/\varepsilon}{C_{DES} \Delta_{max}} \right)$$

PARTITION OF TURBULENT KINETIC ENERGY




FIGURE: Energy spectrum.

OBJECT OF THE PRESENT WORK

OBJECT OF THE PRESENT WORK

- ▶ To control – limit – how the fast energy partition (i.e. the cut-off) changes in physical space

OBJECT OF THE PRESENT WORK

- ▶ To control – limit – how the fast energy partition (i.e. the cut-off) changes in physical space
- ▶ i.e. limit $\frac{\partial \kappa_c}{\partial x_j}$

OBJECT OF THE PRESENT WORK

- ▶ To control – limit – how the fast energy partition (i.e. the cut-off) changes in physical space
- ▶ i.e. limit $\frac{\partial \kappa_c}{\partial x_j}$
- ▶ by limiting $\psi = \max \left(1, \frac{k^{3/2}/\varepsilon}{C_{DES} \Delta_{max}} \right)$

OBJECT OF THE PRESENT WORK

- ▶ To control – limit – how the fast energy partition (i.e. the cut-off) changes in physical space
- ▶ i.e. limit $\frac{\partial \kappa_c}{\partial x_j}$
- ▶ by limiting $\psi = \max \left(1, \frac{k^{3/2}/\varepsilon}{C_{DES} \Delta_{max}} \right)$
- ▶ i.e. limiting the dissipation term, $\psi \varepsilon$, in the k equation

PERTURBATION ANALYSIS

PERTURBATION ANALYSIS

- ▶ Along mean streamlines, k_M and ε_M are assumed to be in equilibrium. We get



$$\frac{dk_M}{dt} = P^k + D^k - \psi \varepsilon_M = 0$$

$$\frac{d\varepsilon_M}{dt} = C_{\varepsilon 1} \frac{\varepsilon_M}{k_M} P^k + D^\varepsilon - C_{\varepsilon 2} \frac{\varepsilon_M^2}{k_M} = 0$$

PERTURBATION ANALYSIS

- ▶ Along mean streamlines, k_M and ε_M are assumed to be in equilibrium. We get



$$\frac{dk_M}{dt} = P^k + D^k - \psi \varepsilon_M = 0$$

$$\frac{d\varepsilon_M}{dt} = C_{\varepsilon 1} \frac{\varepsilon_M}{k_M} P^k + D^\varepsilon - C_{\varepsilon 2} \frac{\varepsilon_M^2}{k_M} = 0$$

- ▶ For infinitesimal perturbations we get

$$0 = \delta P^k + \delta D^k - \varepsilon_M \delta \psi$$

$$0 = C_{\varepsilon 1} \frac{\varepsilon_M}{k_M} P^k \left(\frac{\delta P^k}{P^k} - \frac{\delta k_M}{k_M} \right) + C_{\varepsilon 2} \frac{\varepsilon_M^2}{k_M} \left(\frac{\delta k_M}{k_M} \right) + \delta D^\varepsilon$$

PERTURBATION ANALYSIS

- ▶ Along mean streamlines, k_M and ε_M are assumed to be in equilibrium. We get



$$\frac{dk_M}{dt} = P^k + D^k - \psi \varepsilon_M = 0$$

$$\frac{d\varepsilon_M}{dt} = C_{\varepsilon 1} \frac{\varepsilon_M}{k_M} P^k + D^\varepsilon - C_{\varepsilon 2} \frac{\varepsilon_M^2}{k_M} = 0$$

- ▶ For infinitesimal perturbations we get

$$0 = \delta P^k + \delta D^k - \varepsilon_M \delta \psi$$

$$0 = C_{\varepsilon 1} \frac{\varepsilon_M}{k_M} P^k \left(\frac{\delta P^k}{P^k} - \frac{\delta k_M}{k_M} \right) + C_{\varepsilon 2} \frac{\varepsilon_M^2}{k_M} \left(\frac{\delta k_M}{k_M} \right) + \delta D^\varepsilon$$

$$0 = \delta \varepsilon_M$$

PERTURBATION ANALYSIS

- ▶ Along mean streamlines, k_M and ε_M are assumed to be in equilibrium. We get



$$\frac{dk_M}{dt} = P^k + D^k - \psi \varepsilon_M = 0$$

$$\frac{d\varepsilon_M}{dt} = C_{\varepsilon 1} \frac{\varepsilon_M}{k_M} P^k + D^\varepsilon - C_{\varepsilon 2} \frac{\varepsilon_M^2}{k_M} = 0$$

- ▶ For infinitesimal perturbations we get

$$0 = \delta P^k + \delta D^k - \varepsilon_M \delta \psi$$

$$0 = C_{\varepsilon 1} \frac{\varepsilon_M}{k_M} P^k \left(\frac{\delta P^k}{P^k} - \frac{\delta k_M}{k_M} \right) + C_{\varepsilon 2} \frac{\varepsilon_M^2}{k_M} \left(\frac{\delta k_M}{k_M} \right) + \delta D^\varepsilon$$

$$0 = \delta \varepsilon_M$$

- ▶ 5 Eqns, 7 Unknowns: $\delta \varepsilon_M, \delta P^k, \delta \psi, \delta k_M, \delta \varepsilon_M, \delta D^k, \delta D^\varepsilon$

PERTURBATION ANALYSIS

PERTURBATION ANALYSIS

► $D^k, D^\varepsilon?$

PERTURBATION ANALYSIS

- ▶ $D^k, D^\varepsilon?$
- ▶ Boussinesq and neglecting quadratic perturbation terms gives

PERTURBATION ANALYSIS

- ▶ $D^k, D^\varepsilon?$
- ▶ Boussinesq and neglecting quadratic perturbation terms gives
- ▶

$$\underline{D^k} + \delta D^k = \frac{C_\mu}{\sigma_k} \frac{\partial}{\partial x_j} \left[\frac{k_M^2}{\varepsilon_M} \frac{\partial k_M}{\partial x_j} + \frac{k_M^2}{\varepsilon_M} \frac{\partial(\delta k_M)}{\partial x_j} + \frac{2(\delta k_M)k_M}{\varepsilon_M} \frac{\partial k_M}{\partial x_j} \right]$$

PERTURBATION ANALYSIS

- ▶ $D^k, D^\varepsilon?$
- ▶ Boussinesq and neglecting quadratic perturbation terms gives
- ▶

$$\underline{D^k} + \delta D^k = \frac{C_\mu}{\sigma_k} \frac{\partial}{\partial x_j} \left[\frac{k_M^2}{\varepsilon_M} \frac{\partial k_M}{\partial x_j} + \frac{k_M^2}{\varepsilon_M} \frac{\partial(\delta k_M)}{\partial x_j} + \frac{2(\delta k_M)k_M}{\varepsilon_M} \frac{\partial k_M}{\partial x_j} \right]$$

Following [5], we assume that $\delta k_M/k_M$ does not vary in space, i.e.

PERTURBATION ANALYSIS

- ▶ D^k, D^ε ?
- ▶ Boussinesq and neglecting quadratic perturbation terms gives
- ▶

$$\underline{D^k} + \delta D^k = \frac{C_\mu}{\sigma_k} \frac{\partial}{\partial x_j} \left[\frac{k_M^2}{\varepsilon_M} \frac{\partial k_M}{\partial x_j} + \frac{k_M^2}{\varepsilon_M} \frac{\partial(\delta k_M)}{\partial x_j} + \frac{2(\delta k_M)k_M}{\varepsilon_M} \frac{\partial k_M}{\partial x_j} \right]$$

Following [5], we assume that $\delta k_M/k_M$ does not vary in space, i.e.

$$\frac{\partial(\delta k_M/k_M)}{\partial x_j} = 0 \Rightarrow \frac{\partial(\delta k_M)}{\partial x_j} = \frac{\delta k_M}{k_M} \frac{\partial k_M}{\partial x_j} \Rightarrow$$

PERTURBATION ANALYSIS

- ▶ D^k, D^ε ?
- ▶ Boussinesq and neglecting quadratic perturbation terms gives
- ▶

$$\underline{D^k} + \delta D^k = \frac{C_\mu}{\sigma_k} \frac{\partial}{\partial x_j} \left[\frac{k_M^2}{\varepsilon_M} \frac{\partial k_M}{\partial x_j} + \frac{k_M^2}{\varepsilon_M} \frac{\partial(\delta k_M)}{\partial x_j} + \frac{2(\delta k_M)k_M}{\varepsilon_M} \frac{\partial k_M}{\partial x_j} \right]$$

Following [5], we assume that $\delta k_M/k_M$ does not vary in space, i.e.

$$\begin{aligned} \frac{\partial(\delta k_M/k_M)}{\partial x_j} = 0 &\Rightarrow \frac{\partial(\delta k_M)}{\partial x_j} = \frac{\delta k_M}{k_M} \frac{\partial k_M}{\partial x_j} \Rightarrow \\ \frac{\delta D^k}{D^k} &= \frac{3\delta k_M}{k_M} \quad \frac{\delta D^\varepsilon}{D^\varepsilon} = \frac{2\delta k_M}{k_M} \end{aligned}$$

PERTURBATION ANALYSIS: FINAL STEP

PERTURBATION ANALYSIS: FINAL STEP

- ▶ 7 Eqns, 7 Unknowns:

PERTURBATION ANALYSIS: FINAL STEP

- ▶ 7 Eqns, 7 Unknowns: The perturbation analysis gives $[4, 2]$

PERTURBATION ANALYSIS: FINAL STEP

- ▶ 7 Eqns, 7 Unknowns: The perturbation analysis gives [4, 2]

$$\frac{\delta\psi}{\psi} = \frac{3\delta k_M}{k_M} \left(1 - \frac{C_{\epsilon 2}}{C_{\epsilon 1}\psi} \right), \quad \psi = \max \left(1, \frac{k^{3/2}/\epsilon}{C_{DES}\Delta_{max}} \right)$$

PERTURBATION ANALYSIS: FINAL STEP

- ▶ 7 Eqns, 7 Unknowns: The perturbation analysis gives [4, 2]

$$\frac{\delta\psi}{\psi} = \frac{3\delta k_M}{k_M} \left(1 - \frac{C_{\epsilon 2}}{C_{\epsilon 1}\psi}\right), \quad \psi = \max\left(1, \frac{k^{3/2}/\epsilon}{C_{DES}\Delta_{max}}\right)$$

- ▶ For $\psi < C_{\epsilon 2}/C_{\epsilon 1}$: an increase in ψ (a decrease in Δ_{max}) \Rightarrow negative δk_M (i.e. less modeled and more resolved)

PERTURBATION ANALYSIS: FINAL STEP

- ▶ 7 Eqns, 7 Unknowns: The perturbation analysis gives [4, 2]

$$\frac{\delta\psi}{\psi} = \frac{3\delta k_M}{k_M} \left(1 - \frac{C_{\varepsilon 2}}{C_{\varepsilon 1}\psi} \right), \quad \psi = \max \left(1, \frac{k^{3/2}/\varepsilon}{C_{DES}\Delta_{max}} \right)$$

- ▶ For $\psi < C_{\varepsilon 2}/C_{\varepsilon 1}$: an increase in ψ (a decrease in Δ_{max}) \Rightarrow negative δk_M (i.e. less modeled and more resolved)
- ▶ But for $\psi > C_{\varepsilon 2}/C_{\varepsilon 1}$ this relation is reversed.

PERTURBATION ANALYSIS: FINAL STEP

- ▶ 7 Eqns, 7 Unknowns: The perturbation analysis gives [4, 2]

$$\frac{\delta\psi}{\psi} = \frac{3\delta k_M}{k_M} \left(1 - \frac{C_{\epsilon 2}}{C_{\epsilon 1}\psi}\right), \quad \psi = \max\left(1, \frac{k^{3/2}/\epsilon}{C_{DES}\Delta_{max}}\right)$$

- ▶ For $\psi < C_{\epsilon 2}/C_{\epsilon 1}$: an increase in ψ (a decrease in Δ_{max}) \Rightarrow negative δk_M (i.e. less modeled and more resolved)
- ▶ But for $\psi > C_{\epsilon 2}/C_{\epsilon 1}$ this relation is reversed.
- ▶ Hence we introduce a limit: $\psi \leq C_{\epsilon 2}/C_{\epsilon 1}$

PERTURBATION ANALYSIS: FINAL STEP

- ▶ 7 Eqns, 7 Unknowns: The perturbation analysis gives [4, 2]

$$\frac{\delta\psi}{\psi} = \frac{3\delta k_M}{k_M} \left(1 - \frac{C_{\epsilon 2}}{C_{\epsilon 1}\psi}\right), \quad \psi = \max\left(1, \frac{k^{3/2}/\epsilon}{C_{DES}\Delta_{max}}\right)$$

- ▶ For $\psi < C_{\epsilon 2}/C_{\epsilon 1}$: an increase in ψ (a decrease in Δ_{max}) \Rightarrow negative δk_M (i.e. less modeled and more resolved)
- ▶ But for $\psi > C_{\epsilon 2}/C_{\epsilon 1}$ this relation is reversed.
- ▶ Hence we introduce a limit: $\psi \leq C_{\epsilon 2}/C_{\epsilon 1} \equiv 1.9/1.5 = 1.27$

PARTITION OF TURBULENT KINETIC ENERGY




FIGURE: Energy spectrum.

PERTURBATION ANALYSIS: RETAINING CONVECTION

PERTURBATION ANALYSIS: RETAINING CONVECTION

- Above we set the convection to zero, i.e.

$$\frac{dk_M}{dt} = P^k + D^k - \psi \varepsilon_M = 0$$

$$\frac{d\varepsilon_M}{dt} = C_{\varepsilon 1} \frac{\varepsilon_M}{k_M} P^k + D^\varepsilon - C_{\varepsilon 2} \frac{\varepsilon_M^2}{k_M} = 0$$

PERTURBATION ANALYSIS: RETAINING CONVECTION

- Above we set the convection to zero, i.e.

$$\frac{dk_M}{dt} = P^k + D^k - \psi \varepsilon_M = 0$$

$$\frac{d\varepsilon_M}{dt} = C_{\varepsilon 1} \frac{\varepsilon_M}{k_M} P^k + D^\varepsilon - C_{\varepsilon 2} \frac{\varepsilon_M^2}{k_M} = 0$$

- Now let's keep it and neglect the diffusion ($D^k = D^\varepsilon = 0$), i.e.

$$P^k - C^k - \psi \varepsilon_M = 0, \quad C_{\varepsilon 1} \frac{\varepsilon_M}{k_M} P^k - C^\varepsilon - C_{\varepsilon 2} \frac{\varepsilon_M^2}{k_M} = 0$$

PERTURBATION ANALYSIS: RETAINING CONVECTION

- Above we set the convection to zero, i.e.

$$\frac{dk_M}{dt} = P^k + D^k - \psi \varepsilon_M = 0$$

$$\frac{d\varepsilon_M}{dt} = C_{\varepsilon 1} \frac{\varepsilon_M}{k_M} P^k + D^\varepsilon - C_{\varepsilon 2} \frac{\varepsilon_M^2}{k_M} = 0$$

- Now let's keep it and neglect the diffusion ($D^k = D^\varepsilon = 0$), i.e.

$$P^k - C^k - \psi \varepsilon_M = 0, \quad C_{\varepsilon 1} \frac{\varepsilon_M}{k_M} P^k - C^\varepsilon - C_{\varepsilon 2} \frac{\varepsilon_M^2}{k_M} = 0$$

- The perturbation analysis gives [\[2\]](#)

$$\frac{\delta \psi}{\psi} = \frac{\delta k_M}{k_M} \left(1 - \frac{C_{\varepsilon 2}}{C_{\varepsilon 1} \psi} \right) \qquad D^k = D^\varepsilon = 0$$

PERTURBATION ANALYSIS: RETAINING CONVECTION

- Above we set the convection to zero, i.e.

$$\frac{dk_M}{dt} = P^k + D^k - \psi \varepsilon_M = 0$$

$$\frac{d\varepsilon_M}{dt} = C_{\varepsilon 1} \frac{\varepsilon_M}{k_M} P^k + D^\varepsilon - C_{\varepsilon 2} \frac{\varepsilon_M^2}{k_M} = 0$$

- Now let's keep it and neglect the diffusion ($D^k = D^\varepsilon = 0$), i.e.

$$P^k - C^k - \psi \varepsilon_M = 0, \quad C_{\varepsilon 1} \frac{\varepsilon_M}{k_M} P^k - C^\varepsilon - C_{\varepsilon 2} \frac{\varepsilon_M^2}{k_M} = 0$$

- The perturbation analysis gives [2]

$$\frac{\delta \psi}{\psi} = \frac{\delta k_M}{k_M} \left(1 - \frac{C_{\varepsilon 2}}{C_{\varepsilon 1} \psi} \right) \qquad D^k = D^\varepsilon = 0$$

$$\frac{\delta \psi}{\psi} = 3 \frac{\delta k_M}{k_M} \left(1 - \frac{C_{\varepsilon 2}}{C_{\varepsilon 1} \psi} \right) \qquad C^k = C^\varepsilon = 0$$

PERTURBATION ANALYSIS: RETAINING CONVECTION

- Above we set the convection to zero, i.e.

$$\frac{dk_M}{dt} = P^k + D^k - \psi \varepsilon_M = 0$$

$$\frac{d\varepsilon_M}{dt} = C_{\varepsilon 1} \frac{\varepsilon_M}{k_M} P^k + D^\varepsilon - C_{\varepsilon 2} \frac{\varepsilon_M^2}{k_M} = 0$$

- Now let's keep it and neglect the diffusion ($D^k = D^\varepsilon = 0$), i.e.

$$P^k - C^k - \psi \varepsilon_M = 0, \quad C_{\varepsilon 1} \frac{\varepsilon_M}{k_M} P^k - C^\varepsilon - C_{\varepsilon 2} \frac{\varepsilon_M^2}{k_M} = 0$$

- The perturbation analysis gives [2]

$$\frac{\delta \psi}{\psi} = \frac{\delta k_M}{k_M} \left(1 - \frac{C_{\varepsilon 2}}{C_{\varepsilon 1} \psi} \right) \quad D^k = D^\varepsilon = 0$$

$$\frac{\delta \psi}{\psi} = 3 \frac{\delta k_M}{k_M} \left(1 - \frac{C_{\varepsilon 2}}{C_{\varepsilon 1} \psi} \right) \quad C^k = C^\varepsilon = 0$$

- Same limit: $\psi \leq C_{\varepsilon 2}/C_{\varepsilon 1}$

THE TURBULENCE MODEL

THE TURBULENCE MODEL

- The AKN low-Reynolds number of Abe *et al.* [1] is used as underlying RANS model

$$\frac{\partial k}{\partial t} + \frac{\partial \bar{u}_j k}{\partial x_j} = \frac{\partial}{\partial x_j} \left[\left(\nu + \frac{\nu_t}{\sigma_k} \right) \frac{\partial k}{\partial x_j} \right] + P_k - \psi \varepsilon$$

$$\frac{\partial \varepsilon}{\partial t} + \frac{\partial \bar{u}_j \varepsilon}{\partial x_j} = \frac{\partial}{\partial x_j} \left[\left(\nu + \frac{\nu_t}{\sigma_\varepsilon} \right) \frac{\partial \varepsilon}{\partial x_j} \right] + C_{\varepsilon 1} f_1 P_k \frac{\varepsilon}{k} - C_{\varepsilon 2} \frac{\varepsilon^2}{k}$$

$$C_{\varepsilon 1} = 1.5, \quad C_{\varepsilon 2} = 1.9, \quad C_\mu = 0.09$$

$$\nu_t = C_\mu f_\mu \frac{k^2}{\varepsilon}, \quad \sigma_k = 1.4, \quad \sigma_\varepsilon = 1.4$$

THE TURBULENCE MODEL

- ▶ The AKN low-Reynolds number of Abe *et al.* [1] is used as underlying RANS model

$$\begin{aligned}\frac{\partial k}{\partial t} + \frac{\partial \bar{u}_j k}{\partial x_j} &= \frac{\partial}{\partial x_j} \left[\left(\nu + \frac{\nu_t}{\sigma_k} \right) \frac{\partial k}{\partial x_j} \right] + P_k - \psi \varepsilon \\ \frac{\partial \varepsilon}{\partial t} + \frac{\partial \bar{u}_j \varepsilon}{\partial x_j} &= \frac{\partial}{\partial x_j} \left[\left(\nu + \frac{\nu_t}{\sigma_\varepsilon} \right) \frac{\partial \varepsilon}{\partial x_j} \right] + C_{\varepsilon 1} f_1 P_k \frac{\varepsilon}{k} - C_{\varepsilon 2} \frac{\varepsilon^2}{k} \\ C_{\varepsilon 1} &= 1.5, \quad C_{\varepsilon 2} = 1.9, \quad C_\mu = 0.09 \\ \nu_t &= C_\mu f_\mu \frac{k^2}{\varepsilon}, \quad \sigma_k = 1.4, \quad \sigma_\varepsilon = 1.4\end{aligned}$$

- ▶ together with IDDES of Shur *et al.* [10]
- ▶ With $\psi \leq C_{\varepsilon 2}/C_{\varepsilon 1}$ is called IDDES-PC (Partition Control)

THE NUMERICAL METHOD

THE NUMERICAL METHOD

- ▶ The **Python** finite volume code **pyCALC-LES** [3] is used.

THE NUMERICAL METHOD

- ▶ The **Python** finite volume code **pyCALC-LES** [3] is used.
- ▶ Fully vectorized (i.e. no for loops).

THE NUMERICAL METHOD

- ▶ The **Python** finite volume code **pyCALC-LES** [3] is used.
- ▶ Fully vectorized (i.e. no for loops).
- ▶ Fractional step. For velocities, second-order central differencing in space and Crank-Nicolson in time.

THE NUMERICAL METHOD

- ▶ The **Python** finite volume code **pyCALC-LES** [3] is used.
- ▶ Fully vectorized (i.e. no for loops).
- ▶ Fractional step. For velocities, second-order central differencing in space and Crank-Nicolson in time.
- ▶ For k and ε , hybrid central/upwind scheme

THE NUMERICAL METHOD

- ▶ The **Python** finite volume code **pyCALC-LES** [3] is used.
- ▶ Fully vectorized (i.e. no `for` loops).
- ▶ Fractional step. For velocities, second-order central differencing in space and Crank-Nicolson in time.
- ▶ For k and ε , hybrid central/upwind scheme
- ▶ The discretized equations are solved with **Python sparse matrix solvers**.

THE NUMERICAL METHOD

- ▶ The **Python** finite volume code **pyCALC-LES** [3] is used.
- ▶ Fully vectorized (i.e. no for loops).
- ▶ Fractional step. For velocities, second-order central differencing in space and Crank-Nicolson in time.
- ▶ For k and ε , hybrid central/upwind scheme
- ▶ The discretized equations are solved with **Python sparse matrix solvers**.
- ▶ The **pyAMG** solver [9] is used for the pressure Poisson equation (very efficient)

THE NUMERICAL METHOD


- ▶ The **Python** finite volume code **pyCALC-LES** [3] is used.
- ▶ Fully vectorized (i.e. no for loops).
- ▶ Fractional step. For velocities, second-order central differencing in space and Crank-Nicolson in time.
- ▶ For k and ε , hybrid central/upwind scheme
- ▶ The discretized equations are solved with **Python sparse matrix solvers**.
- ▶ The **pyAMG** solver [9] is used for the pressure Poisson equation (very efficient)

CHANNEL FLOW, PERIODIC B.C.


- ▶ $Re_\tau = u_\tau h / \nu = 5\,200$
- ▶ The mesh has $32 \times 96 \times 32$ (x, y, z) cells \Rightarrow
 $(\Delta x^+, \Delta z^+) = (800, 400)$.

CHANNEL FLOW, PERIODIC B.C.


- ▶ $Re_\tau = u_\tau h / \nu = 5\,200$
- ▶ The mesh has $32 \times 96 \times 32$ (x, y, z) cells $\Rightarrow (\Delta x^+, \Delta z^+) = (800, 400)$.



(A) Mean velocity.



(B) ψ



(C) Turbulent viscosity


FIGURE: — : IDDES-PC model; - - : IDDES; Markers: DNS [8]

CHANNEL FLOW INLET-OUTLET


- ▶ RANS inlet values on k and ε .

CHANNEL FLOW INLET-OUTLET


- RANS inlet values on k and ε .



(A) Modeled k .



(B) ψ .



(C) Turbulent viscosity.


FIGURE: Profiles at $x = \delta$, i.e. one half-channel width.

HUMP FLOW


- ▶ The Reynolds number is $Re_c = 936\,000$
- ▶ The spanwise extent is $z_{max} = 0.2$.
- ▶ The mesh has $582 \times 128 \times 32$ cells (x, y, z)

HUMP FLOW


- ▶ The Reynolds number is $Re_c = 936\,000$
- ▶ The spanwise extent is $z_{max} = 0.2$.
- ▶ The mesh has $582 \times 128 \times 32$ cells (x, y, z)



(A) Grid.




(B) Pressure coefficient.




(C) Skin friction

FIGURE: — : IDDES-PC model; - - . IDDES. Markers: experiments [7, 6]


HUMP FLOW. VELOCITIES.



(A) $x = 0.65$.




(B) $x = 1.0$.




(C) $x = 1.30$.

FIGURE: — : IDDES-PC model; - - : IDDES. Markers: experiments [7, 6]


HUMP FLOW. SHEAR STRESSES.



(A) $x = 0.65$.




(B) $x = 1.0$.



(C) $x = 1.30$.

FIGURE: — : IDDES-PC model; - - : IDDES. Markers: experiments [7, 6]

HUMP FLOW. TURBULENT VISCOSITY AND $\langle u'u' \rangle$.



(A) Grid.

(B) Streamwise fluctuations.

(C) Turbulent viscosity.

FIGURE: $x = 0$. — : IDDES-PC model; - - . IDDES.

CONCLUSIONS

- ▶ A limiter on $\psi = \max\left(1, \frac{k^{3/2}/\varepsilon}{C_{DES}\Delta_{max}}\right)$ is proposed which reads

CONCLUSIONS

- ▶ A limiter on $\psi = \max\left(1, \frac{k^{3/2}/\varepsilon}{C_{DES}\Delta_{max}}\right)$ is proposed which reads
- ▶ $\psi \leq C_{\varepsilon 2}/C_{\varepsilon 1}$

CONCLUSIONS

- ▶ A limiter on $\psi = \max\left(1, \frac{k^{3/2}/\varepsilon}{C_{DES}\Delta_{max}}\right)$ is proposed which reads
- ▶ $\psi \leq C_{\varepsilon 2}/C_{\varepsilon 1} \equiv 1.9/1.5 = 1.27$

CONCLUSIONS

- ▶ A limiter on $\psi = \max\left(1, \frac{k^{3/2}/\varepsilon}{C_{DES}\Delta_{max}}\right)$ is proposed which reads
- ▶ $\psi \leq C_{\varepsilon 2}/C_{\varepsilon 1} \equiv 1.9/1.5 = 1.27$
- ▶ The limiter is derived using perturbation analysis which assumes

$$\frac{\partial(\delta k_M)}{\partial x_j} = \frac{\delta k_M}{k_M} \frac{\partial k_M}{\partial x_j}$$

CONCLUSIONS

- ▶ A limiter on $\psi = \max\left(1, \frac{k^{3/2}/\varepsilon}{C_{DES}\Delta_{max}}\right)$ is proposed which reads
- ▶ $\psi \leq C_{\varepsilon 2}/C_{\varepsilon 1} \equiv 1.9/1.5 = 1.27$
- ▶ The limiter is derived using perturbation analysis which assumes

$$\frac{\partial(\delta k_M)}{\partial x_j} = \frac{\delta k_M}{k_M} \frac{\partial k_M}{\partial x_j}$$

- ▶ The limiter is shown to reduce $\frac{\partial(\delta k_M)}{\partial x_j}$



CONCLUSIONS

- ▶ A limiter on $\psi = \max\left(1, \frac{k^{3/2}/\varepsilon}{C_{DES}\Delta_{max}}\right)$ is proposed which reads
- ▶ $\psi \leq C_{\varepsilon 2}/C_{\varepsilon 1} \equiv 1.9/1.5 = 1.27$
- ▶ The limiter is derived using perturbation analysis which assumes

$$\frac{\partial(\delta k_M)}{\partial x_j} = \frac{\delta k_M}{k_M} \frac{\partial k_M}{\partial x_j}$$

- ▶ The limiter is shown to reduce $\frac{\partial(\delta k_M)}{\partial x_j}$
- ▶ Good results are obtained (better than standard IDDES for the hump flow)

REFERENCES I

- [1] K. Abe, T. Kondoh, and Y. Nagano. A new turbulence model for predicting fluid flow and heat transfer in separating and reattaching flows - 1. Flow field calculations. *Int. J. Heat Mass Transfer*, 37(1):139–151, 1994.
- [2] L. Davidson. Fluid mechanics, turbulent flow and turbulence modeling . eBook, Division of Fluid Dynamics, Dept. of Mechanics and Maritime Sciences, Chalmers University of Technology, Gothenburg, 2021.
- [3] L. Davidson. pyCALC-LES: a Python code for DNS, LES and Hybrid LES-RANS . Division of Fluid Dynamics, Dept. of Mechanics and Maritime Sciences, Chalmers University of Technology, Gothenburg, 2021.
- [4] C. Friess and L. Davidson. A formulation of PANS able to mimic IDDES. *International Journal of Heat and Fluid Flow*, 86(108666), 2020.

REFERENCES II

- [5] C. Friess, R. Manceau, and T.B. Gatski. Toward an equivalence criterion for hybrid RANS/LES methods. *International Journal of Heat and Fluid Flow*, 122:233–246, 2015.
- [6] D. Greenblatt, K. B. Paschal, C.-S. Yao, and J. Harris. A separation control CFD validation test case Part 1: Zero efflux oscillatory blowing. AIAA-2005-0485, 2005.
- [7] D. Greenblatt, K. B. Paschal, C.-S. Yao, J. Harris, N. W. Schaeffler, and A. E. Washburn. A separation control CFD validation test case. Part 1: Baseline & steady suction. AIAA-2004-2220, 2004.
- [8] M. Lee and R. D. Moser. Direct numerical simulation of turbulent channel flow up to $Re_\tau \approx 5200$. *Journal of Fluid Mechanics*, 774:395–415, 2015.
- [9] L. N. Olson and J. B. Schroder. PyAMG: Algebraic multigrid solvers in Python v4.0, 2018. Release 4.0.

REFERENCES III

- [10] M. L. Shur, P. R. Spalart, M. Kh. Strelets, and A. K. Travin. A hybrid RANS-LES approach with delayed-DES and wall-modelled LES capabilities. *International Journal of Heat and Fluid Flow*, 29:1638–1649, 2008.